

1. Identification

Product number	BPSW-3726-2188
Product identifier	GET THE ICE OFF DE-ICER
Company information	Bullseye Products LLC 3595 Polaris Ave Las Vegas, NV 89103 United States
Company phone	302-468-5086
Emergency telephone US	800-255-3924
Version #	01
Recommended use	De-Icer
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Acute toxicity, oral	Category 3
	Acute toxicity, dermal	Category 3
	Acute toxicity, inhalation	Category 3
	Germ cell mutagenicity	Category 1B
	Reproductive toxicity	Category 1B
	Specific target organ toxicity, single exposure	Category 2
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled. May damage fertility or the unborn child. Causes damage to organs.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor. Specific treatment (see this label). Rinse mouth. Take off immediately all contaminated clothing and wash it before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methanol		67-56-1	60 - 80
Ethylene Glycol		107-21-1	2.5 - 10
Isopropyl Alcohol		67-63-0	2.5 - 10
Carbon Dioxide		124-38-9	1 - 2.5
Propane		74-98-6	1 - 2.5
Other components below reportable levels			10 - 20

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.

Skin contact

Take off immediately all contaminated clothing. Wash off with soap and plenty of water. Call a POISON CENTER or doctor/physician if you feel unwell. For minor skin contact, avoid spreading material on unaffected skin.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Powder. Alcohol resistant foam. Water. Carbon dioxide (CO₂).

Unsuitable extinguishing media

None known.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Ground and bond containers when transferring material. Do not re-use empty containers. Do not breathe gas. Do not taste or swallow. Avoid contact with skin. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Avoid contact with clothing. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B) Exposure controls/personal protection

8. Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m ³
		5000 ppm
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m ³
		400 ppm
Methanol (CAS 67-56-1)	PEL	260 mg/m ³
		200 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m ³
		1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	Aerosol.
	TWA	5000 ppm	
	Ceiling	100 mg/m ³	
Ethylene Glycol (CAS 107-21-1)	STEL	400 ppm	
	TWA	200 ppm	
Isopropyl Alcohol (CAS 67-63-0)	STEL	250 ppm	
	TWA	200 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m ³
		30000 ppm
	TWA	9000 mg/m ³
Isopropyl Alcohol (CAS 67-63-0)		5000 ppm
	STEL	1225 mg/m ³
	TWA	500 ppm
		980 mg/m ³

GET THE ICE OFF DE-ICER SAFETY DATA SHEET

Methanol (CAS 67-56-1)	STEL	400 ppm 325 mg/m ³
	TWA	250 ppm 260 mg/m ³
Propane (CAS 74-98-6)	TWA	200 ppm 1800 mg/m ³ 1000 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1) Skin designation applies.

US - Tennessee OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Wear a full-face respirator, if needed.

Hand protection Wear protective gloves.

Skin protection

Other Wear appropriate chemical resistant clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Clear.
Physical state	Liquid.
Form	Aerosol.
Color	Colorless.
Odor	Solvent.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C) estimated

Flash point -156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Flammability limit - upper (%)
6 % estimated

33.2 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 65 - 85 psig @70F estimated

Vapor density Not available.

Relative density 0.811 g/cm3 estimated

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature 857.76 °F (458.76 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 0.81 g/cm3 estimated

Flame extension 18 in estimated

Flammability class Flammable IB estimated

Heat of combustion 28.84 kJ/g estimated

Heat of combustion (NFPA 30B) 16.39 kJ/g estimated

Percent volatile 98.49 % estimated

Specific gravity 0.811 estimated

VOC (Weight %) 80.65 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Avoid temperatures exceeding the flash point.

Incompatible materials Strong oxidizing agents. Isocyanates. Chlorine.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Toxic if swallowed.

Inhalation Toxic by inhalation. May cause damage to organs by inhalation.

Skin contact Toxic in contact with skin.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Toxic by inhalation. Toxic if swallowed. Toxic in contact with skin.

Components	Species	Test Results
Ethylene Glycol (CAS 107-21-1)		
Acute		
<i>Dermal</i>		
LD50	Mouse	> 3500 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 2.5 mg/l, 6 Hours
<i>Oral</i>		
LD50	Rat	7712 mg/kg
Isopropyl Alcohol (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	16.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 10000 ppm, 6 Hours
<i>Oral</i>		
LD50	Rat	5.84 g/kg
Methanol (CAS 67-56-1)		
Acute		
<i>Inhalation</i>		
LC50	Cat	85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours
	Mouse	79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours 82.1 mg/l, 6 Hours
<i>Oral</i>		
LD50	Monkey	6000 mg/kg
	Rat	1187 - 2769 mg/kg
<i>Other</i>		
LD50	Mouse	6000 mg/kg
Propane (CAS 74-98-6)		
Acute Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Respiratory or skin sensitization

Direct contact with eyes may cause temporary irritation.

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity May damage fertility or the unborn child.

Specific target organ toxicity - single exposure Causes damage to organs.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
INDUSTRIAL DE-ICER (CAS Mixture)			
Aquatic			
Algae	IC50	Algae	10050.251 mg/L, 72 Hours estimated
<i>Acute</i>			
Crustacea	EC50	Daphnia	11857.5977 mg/l, 48 hours estimated
Fish	LC50	Fish	12512.8652 mg/l, 96 hours estimated

Components		Species	Test Results
Ethylene Glycol (CAS 107-21-1)			
Aquatic			
Crustacea	EC50	Daphnia	46300 mg/L, 48 Hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	8050 mg/l, 96 hours
Isopropyl Alcohol (CAS 67-63-0)			
Aquatic			
Algae	IC50	Algae	1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	> 1400 mg/l, 96 hours
Methanol (CAS 67-56-1)			
Aquatic			
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	> 100 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Ethylene Glycol	-1.36
Isopropyl Alcohol	0.05
Methanol	-0.77
Propane	2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Methanol (CAS 67-56-1)

U154

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT	UN1950
UN number	Aerosols, flammable
UN proper shipping name	
Transport hazard class(es)	2.1
Class	-
Subsidiary risk	None
Label(s)	Not applicable.
Packing group	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.	
IATA	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Transport hazard class(es)	
Class	2.1
Subsidiary risk	6.1(PGIII)
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10P
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Aircraft Allowed.
Cargo aircraft only Allowed.
Packaging Exceptions LTD QTY

IMDG

UN number UN1950
UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1
Subsidiary risk 6.1(PGIII)
Label(s) 2.1, 6.1
Packing group Not applicable.

Environmental hazards

Marine pollutant No.

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions NOT a LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.



GET THE ICE OFF DE-ICER SAFETY DATA SHEET

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethylene Glycol (CAS 107-21-1) Listed.
Methanol (CAS 67-56-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986(SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methanol	67-56-1	60 - 80
Ethylene Glycol	107-21-1	2.5 - 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylene Glycol (CAS 107-21-1)
Methanol (CAS 67-56-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA)

US state regulations

Not regulated.

US. Massachusetts RTK - Substance List

Carbon Dioxide (CAS 124-38-9)
Ethylene Glycol (CAS 107-21-1)
Isopropyl Alcohol (CAS 67-63-0)
Methanol (CAS 67-56-1)
Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Carbon Dioxide (CAS 124-38-9)
Ethylene Glycol (CAS 107-21-1)
Isopropyl Alcohol (CAS 67-63-0)
Methanol (CAS 67-56-1)
Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon Dioxide (CAS 124-38-9)
Ethylene Glycol (CAS 107-21-1)
Isopropyl Alcohol (CAS 67-63-0)
Methanol (CAS 67-56-1)
Propane (CAS 74-98-6)

US. Rhode Island RTK

Ethylene Glycol (CAS 107-21-1)
Isopropyl Alcohol (CAS 67-63-0)



GET THE ICE OFF DE-ICER SAFETY DATA SHEET

Methanol (CAS 67-56-1)
Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1)

Listed: March 16, 2012

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-30-2015

Version # 01

Disclaimer The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.